

Product Technical Bulletin

Everlast II Traditional

Steel Roofing and Siding Panel

Description

True 28-gauge steel (before paint) with heavy-duty metallic coating is encased in abrasion-busting primer and Siliconized Modified Polyester topcoat to deliver enduring corrosion resistance and longer life. Wider blanks, deeper minor rib heights create a stronger, more durable panel.

Advantages of Everlast II Traditional

- Synergy chalk and fade resistance
- Greater snow and wind yields and hail resistance
- Highly resistant to UV rays, acid rain, salt spray, and abrasion

UL Ratings

- UL construction No# 560 UPLIFT TEST
- UL 2218 Class 4 IMPACT RESISTANCE
- UL 790 Class A FIRE RESISTANCE

Standard Specifications

- 28-gauge (.016) Structural Steel Grade 80 produced in conformance with ASTM792
- 95,000 PSI minimum yield
- Siliconized Modified Polyester Paint System with standard primer
- Heat-formed panels with 3/4" major rib height; 3/16" minor rib height
- 36" cover width
- Custom cut to the inch up to 40' feet
- Available in wide variety of colors
- 3:12 recommended minimum roof pitch
- 40-year non-prorated warranty
- 10-year edge rust warranty
- Cut panels coated with CECI™

Roofing and Siding Applications

- Agricultural
- Architectural
- Commercial
- Industrial
- Residential





Mid-Atlantic 10 Enterprise Court Lebanon, PA 17042 Phone: 717.270.6554 888.339.0059 New England 24 JR Mains Drive Bridgton, ME 04009 Phone: 207.647.5500 800.677.2060

9"

Midwest 7180 N 050 E Howe, IN 46746 Phone: 260.562.3783 866.562.3782 3/4"

36" Cover Width

TRADITIONAL Color Guide

Lebanon, PA 888.339.0059

Bridgton, ME 800.677.2060

Howe, IN 866.562.3782



Colors may vary slightly from actual metal. Painted swatches are available by request.

www.everlastroofing.com

